

Concepts—FEM Package for Elliptic Problems in 2D and 3D

P. Frauenfelder, C. Lage, K. Schmidt, C. Schwab

Concept Oriented Design





The numerical methods which should be implemented are already formulated in an abstract way based on hierarchical structured mathematical concepts. Therefore, represent each concept by a module and combine the modules according to the numerical algorithm. This defines [concept oriented design](#).

The Software Package CONCEPTS

[CONCEPTS](#) [3] is designed using *concept oriented design* and written nearly completely in [C++](#). It is used for [BEM](#) [4], [hp FEM](#) and [DGFM](#).

Results: Exponential Convergence

Solving the [Maxwell Eigen value problem](#) in a perfect conductor boundary condition domain $\Omega = (-1, 1)^3 \setminus (-1, 0)^3$ (so called Fichera corner) with $\varepsilon = \mu = 1$ using [weighted regularization](#) [1].



Mathematical Concepts

Find $u \in H_{\Gamma_D}^1(\Omega)$ such that $\forall v \in H_{\Gamma_D}^1(\Omega)$:

$$\underbrace{\int_{\Omega} \nabla u \cdot \nabla v \, dx + \int_{\Omega} uv \, dx}_{=:a(u,v) \text{ bilinear form}} = \underbrace{\int_{\Omega} fv \, dx + \int_{\Gamma_N} g_N v \, ds}_{=:l(v) \text{ linear form}}.$$

Find $u_N \in V_N := S_{\Gamma_D}^{p,1}(\Omega, \mathcal{T})$ such that $\forall v \in V_N$:

$$a(u, v) = l(v).$$

Using a basis $\{\Phi_i\}_{i=1}^N$ of V_N makes it possible to obtain a stiffness matrix $[A]_{ij} = a(\Phi_i, \Phi_j)$ and a load vector $[l]_i = l(\Phi_i)$. The resulting linear system $Au_N = l$ can be solved with a linear solver (*e.g.* conjugate gradients).

Assembling using T matrices: $\Phi_i|_K = \sum_{j=1}^{m_K} [\mathbf{T}_K]_{ji} \varphi_j^K$

$$l = l(\Phi) = \sum_{\tilde{K}} \mathbf{T}_{\tilde{K}}^\top l(\varphi^{\tilde{K}}) = \sum_{\tilde{K}} \mathbf{T}_{\tilde{K}}^\top l_{\tilde{K}}$$

$$A = a(\Phi, \Phi) = \sum_{K, \tilde{K}} \mathbf{T}_{\tilde{K}}^\top a(\varphi^K, \varphi^{\tilde{K}}) \mathbf{T}_K = \sum_{K, \tilde{K}} \mathbf{T}_{\tilde{K}}^\top A_{\tilde{K}K} \mathbf{T}_K$$

The constraints of [hanging nodes](#) are eliminated using S matrices: $\varphi_j^K|_{K'} = \sum_{l=1}^{m_{K'}} [\mathbf{S}_{K'K}]_{lj} \varphi_l^{K'}$ for a $K' \subset K$ generated by a subdivision. $\mathbf{T}_{K'} = \mathbf{S}_{K'K} \mathbf{T}_K + \tilde{\mathbf{T}}_{K'}$ builds the T matrix for K' . The S matrices for quads and hexahedra can be built with tensor products from 1D S matrices. This makes [anisotropic refinements](#) possible.


References

- [1] M. COSTABEL, M. DAUGE. [Weighted regularization of Maxwell equations in polyhedral domains](#). *Numer. Math.* **93**(2) (2002) 239–277.
- [2] P. FRAUENFELDER, C. LAGE. [Concepts—an object-oriented software package for partial differential equations](#). *M2AN* **36**(5) (2002) 937–951.
- [3] C. LAGE, P. FRAUENFELDER, G. SCHMIDLIN ET. AL. [Concepts—C++ Class Library for Elliptic Problems](#), <http://www.math.ethz.ch/~concepts/>.
- [4] G. SCHMIDLIN. [Fast Solution Algorithms for Integral Equations in \$\mathbb{R}^3\$](#) . PhD thesis, Swiss Federal Institute of Technology Zurich, 2003.


Seminar for Applied Mathematics, ETH Zürich

Fundamental Classes


Bilinear form $a(., .)$ and linear form $l(.)$:




Mesh \mathcal{T} and space V_N :



Assembling the global matrix and the load vector and solving the linear system:



The T matrices are built columnwise: each column in a T matrix corresponds to a global degree of freedom:



S matrices in 1D are computed by solving a linear system. In higher dimensions, tensor product and composition is used:

